

# Furlex Assemblies

Furlex type			Assy # Complete kit		Tube		Box		Wire			Stalok pack. standard	Optional r-screw	Standard terminal	Incl. rigging screw			
Series	Dim Ø mm	Length	With standard terminal	With rigging screw	Part #	Weight / dim. L=2510 mm	Part #	Weight	Length	Part #	Weight	Part #	Part #	Total weight	Total weight			
100S	4	8100	027-019-51	-	539-314-02	4.8 kg ø65 mm	539-352-52	5.7 kg	10500	-	Incl in box	Incl in box	-	10.5 kg	-			
		10500	-52		-03	5.9 kg ø65 mm								11.6 kg				
	5	8100	-53		-02	4.8 kg ø65 mm	-54	6.3 kg	"					12900	11.1 kg	-		
		10500	-54		-03	5.9 kg ø65 mm									12.2 kg			
		12900	-55		-04	7.0 kg ø65 mm		-55							6.7 kg		13.7 kg	
		10500	-56		-03	5.9 kg ø65 mm		-57							7.6 kg		"	13.5 kg
12900	-57	-04	7.0 kg ø65 mm		14.6 kg	15.0 kg												
200S	6	10600	031-021-51	031-021-61	539-565-02	6.7 kg ø85 mm	539-551-11	8.5 kg	13000	601-004-62	2.5 kg	301-601-11	174-536-11	18.3 kg	18.6 kg			
		13000	-52	-62	-03	9.2 kg ø85 mm								20.8 kg	21.1 kg			
		15400	-53	-63	-04	10.7 kg ø85 mm								22.7 kg	23.0 kg			
	7	13000	-54	-64	-03						15400	601-005-62	3.9 kg	301-602-11	174-537-11	22.3 kg	22.5 kg	
		15400	-55	-65	-04						15400					23.8 kg	24.0 kg	
		17800	-56	-66	-04 + -06	+2.5 kg ø65 mm					17800		-63			4.5 kg	26.9 kg	27.1 kg
		15400	-57	-67	-04						15400		601-006-61			5.1 kg	301-603-11	174-538-11
	8	17800	-58	-68	-04 + -06						17800	-62	5.8 kg			28.3 kg	28.6 kg	
		300S	15500	039-027-51	039-027-61	539-265-02			18 kg ø125 mm	539-251-11	12 kg	15500	601-006-63	5.1 kg	301-604-11	174-519-11	36.2 kg	36.7 kg
	17900		-52	-62	-03	20 kg ø125 mm							17900	-64			6 kg	39.1 kg
15500	-53		-63	-02				17900	601-008-62			9.2 kg	301-605-11	174-520-11	40.4 kg	40.9 kg		
17900	-54		-64	-03				20300	-63			10.5 kg			42.4 kg	42.9 kg		
400S	12	17700	049-034-51	049-034-61	539-165-02	30 kg ø 150 mm	539-151-11 & 539-151-12	26.3 kg	20400	601-009-51	15 kg	301-606-11	174-523-11	74.7 kg	75.8 kg			
		20100	-52	-62	+ 1 x -05	+1x4.2 kg ø65mm					"			"	"	78.9 kg	80.0 kg	
		22500	-53	-63	+ 2 x -05	+2x4.2 kg ø65mm					22800			-52	17 kg	85.1 kg	86.2 kg	
	14	20100	-54	-64	+ 1 x -05						20400	601-010-51	21 kg	301-607-11	174-524-11	85.5 kg	87.5 kg	
		22500	-55	-65	+ 2 x -05						22800	-52	25 kg			93.7 kg	95.7 kg	
		23000	060-046-56	060-046-66	539-423-11						23000	601-013-07						
500S	16	27800	-57	-67	+ 1 x -10	Note: 4.8 m sections	539-151-21 & 539-151-22		27800	-08		301-608-11	174-525-11					

Dyform wedges: ø5=301-622-01; ø6=301-623-01; ø7=301-624-01; ø8=301-625-01; ø10=301-626-01; ø12=301-627-01